

140 LXP

Single Panel
Horizontal Sliding
Manual Operation



APPLICATION:

Cleanroom and clean production areas that require frequent washdown/wipedown.

FEATURES:

- High strength 1-3/4" thick lightweight seamless (no center seam) laminated fiberglass panels for easy cleaning. Stainless steel (20 gauge) edge capping for added strength and protection.
- Corrosion-resistant heavy-duty door hardware. Recessed powder coated stainless steel pull handles.
- Top/bottom guidance system positively maintains door seal and position. Ensures fast, controlled operation with minimal gasket wear.
- Adjustable panel hardware for in-field adjustments. Maintains a positive and tight seal.
- Full perimeter, non-marking, non-shedding, non-absorptive gray vinyl blade-type gasket capable of holding a seal under positive/negative pressure.
- **NO** hardware mounted into floor.
- Optional vision panel with sloped one piece stainless steel frame; no visible fasteners.
- Stainless steel sloped shroud conceals rail and operator.
- All visible stainless steel is 304, #4 finish (316 stainless steel optional).



DOOR SIZES:

To maintain the integrity of a seamless (no center seam) construction, the following restrictions apply.

- Up to 10'0" high if maximum width of opening is 7'7" or less.
 - Up to 8'7" high if maximum width of opening is 8'0" or less.
- (Other sizes available - consult factory.)

PANEL CONSTRUCTION:

- Fiberglass sheet laminated to an expanded polystyrene core material.
- 20 gauge stainless steel edge capping.
- Full perimeter gaskets: Non-marking, non-shedding, non-absorptive gray vinyl blade type.

OPERATION:

- Manual.

WARRANTY:

- One year on all components.

OPTIONS:

- Stainless steel clad panel.
- Vision panel (optional sizes).