

240

Single Panel
Horizontal Sliding
Manual Operation



APPLICATION:

Cleanroom and clean production areas that require a controlled environment and frequent washdown/wipedown.



FEATURES:

- Unitized high strength 2" thick molded seamless lightweight fiberglass panel for easy cleaning. Stainless steel (20 gauge) edge capping for added strength and protection.
- Corrosion-resistant heavy-duty door hardware.
Recessed stainless steel pull handles.
- Top/bottom guidance system positively maintains door seal and position.
Ensures fast, controlled operation with minimal gasket wear.
- Adjustable top/bottom panel hardware for in-field adjustments. Maintains a positive and tight seal.
- Full perimeter, non-marking gray vinyl gasket capable of holding a seal under positive/negative pressure.
- Stainless steel sloped shroud conceals rail.]
- Automatic closer with "Hold-Open" feature.

DOOR SIZES:

- 3' x 7' minimum.
- 8' x 8' maximum.
- Other sizes available - consult factory.

PANEL CONSTRUCTION:

- Unitized design.
- Structural molded fiberglass reinforced polyester shells..
- 20 gauge stainless steel edge capping.
- Seamless panel construction.
- Full perimeter gaskets: Non-marking gray vinyl, blade type.

OPERATION:

- Manual with automatic closer and "hold-open" feature.

INSULATION:

- 2" thick poured polyurethane foam, rated R-16.

WARRANTY:

- One year on all components.

OPTIONS:

- Stainless steel clad panel.
- Color (consult factory).
- Vision panel (optional sizes).
- Canebolt.