



Utilizing Environmentally Safe, CFC-free R-134a Refrigerant

Model CBC37-DC Model CBC50-DC



Model CBC64-DC



Model CBC95-DC



Refrigerator

DEEP CHILL HORIZONTAL BOTTLE COOLERS

Standard Features

- Available in 37", 50", 64", 95" Widths
- Design to Hold Product Below 32° F
- · Modern, State-of-the-Art Styling
- Wear Resistant Black Vinyl Coated Steel Exterior with All Stainless Steel Countertop and Slide Lids for Lifetime Durability
- Heavy Duty, Long Lasting Galvanized Steel Interior
- Performance Rated Refrigeration System Utilizing Environmentally Safe R-134a Refrigerant
- Front, Rear and Side Venting Louvers Allow Greater Condenser Air Flow for Tight Fit Installations
- Easily Accessible and Serviceable Slide-Out Condensing Unit
- Automatic, Energy Saving, Non-Electric Condensate Disposal System with Easily Accessible, Front Mounted Cleanout Drainage Hose And Drain Pan
- High Density, Non-CFC Polyurethane Foamed-In-Place Insulation
- Epoxy Coated, Heavy Duty, Adjustable Steel Wire Storage Bin Dividers to Maximize Storage Space
- Heavy Duty Bottle Cap Opener with Extra Capacity, Removable Cap Catcher
- Extra Long 10' Power Supply Cord and Plug Attached
- Automatic Defrosting Period is Timer Initiated

Optional Features & Accessories


- 3 & 4" Locking, Swivel Casters
- 6" Adjustable Legs
- SS Models Stainless Steel Exterior, Galvanized Steel Interior
- · Remote Models


- Additional Bin
- Dividers
- Locking Lids





SPECIFICATIONS CBC37-DC CBC50-DC CBC64-DC CBC95-DC DIMENSIONAL DATA

Net Capacity (cu. ft.)	10.3	15.1	20.3	32.0
Case Capacity – 12 oz. Bottle (# Cases)	12	18	25	40
Case Capacity – 12 oz. Cans (# Cases)	18 1/2	27	37	59
Width, Overall (in.)	37	50	64	95
Depth, Overall (Less Cap Catcher) (in.)	27 1/2	27 1/2	27 1/2	27 1/2
Height, Overall (in.)	33 1/2	33 1/2	33 1/2	33 1/2
Number of Slide Lids	1	2	2	3
Number of Bin Dividers	2	3	4	8
Condensing Unit Size (H.P.)	1/5	1/3	1/3	1/2
Refrigerant	R-134a	R-134A	R-134A	D 1211
Reingerani	R-134a	K-134A	K-134A	R-134A
Cabinet Electrical Specs	115/60/1	115/60/1	115/60/1	115/60/1
-				
Cabinet Electrical Specs	115/60/1	115/60/1	115/60/1	115/60/1
Cabinet Electrical Specs Total Amps	115/60/1 5.2	115/60/1	115/60/1 8.0	115/60/1 10.3
Cabinet Electrical Specs Total Amps Defrost Amps	115/60/1 5.2 4.4	115/60/1 8.0 4.4	115/60/1 8.0 5.2	115/60/1 10.3 6.1
Cabinet Electrical Specs Total Amps Defrost Amps Power Supply Cord	115/60/1 5.2 4.4 YES	115/60/1 8.0 4.4 YES	115/60/1 8.0 5.2 YES	115/60/1 10.3 6.1 YES
Cabinet Electrical Specs Total Amps Defrost Amps Power Supply Cord Shipping Weight (lbs.)	115/60/1 5.2 4.4 YES 215	115/60/1 8.0 4.4 YES 265	115/60/1 8.0 5.2 YES 315	115/60/1 10.3 6.1 YES 435










Note: All specifications subject to change without notice.



A Division of BALMAC International, Inc. 61 Broadway Suite 1900, New York, NY 10006-2701 (212) 898-9699 Fax: (212) 514-9234 www.bmil.com - bmil@bmil.com



CBC Side VIEW